

UFI UPDN Municipal Series String Filters

UFI's UPDN Series Cartridges have been tested and certified to the ANSI/NSF 42/61 standard to assure continuity of materials and consistency in manufacturing the finished product. Each component is identified and controlled in accordance with the registered wetted parts lists. These cartridges will not impart unwanted leached materials into the downstream flow.

Nominal micron ratings of 0.5 to 200, with 3.75" to 72" lengths and 2" to 6" outside diameters, offer a wide range of options suitable to most industry standard filter housings. Cartridges are double open ended. Optional end cap treatments available. See below.

UPDN Cartridges are in use at state and federal correctional institutions, office buildings, municipal water districts, Department of Defense road mobile potable water systems, and other applications where the ANSI/NSF 42/61 standard is required.



This product has been tested and certified according to ANSI/NSF 42 and 61 for material safety only.



Ordering Info

EX: UPDN5R40PSOC = 5micron, 2.5"O.D., 40" long, poly core with 222 o-ring & cap

Media	Micron	O.D.	Length	Core Material	End Treatment	Filter Wrap Options	Qty/Box (2.5"O.D.)
UPDN-NSF42/61 Polypropylene	0.5	T - 2"	3.75"	P - Polypropylene	(P)E - Poly Core Insert SOC - 222 O-Ring & Cap SOF - 222 O-Ring & Fin 06C - 226 O-Ring & Cap 06F - 226 O-Ring & Fin PS - Poly Spring B - Buna Gasket	IW - Individual Bag ISW - Individual Shrink Wrap	60
	1	E - 2-1/4"	4"				60
	3	F - 2-3/8"	5"				60
	5	R - 2-1/2"	6"				30
	10	H - 2-5/8"	7"				30
	15	S - 2-3/4"	8"				30
	20		9"				30
	25	L - 2-7/8"	9.75"				30
	30	P - 3"	10"				30
	40	BB - 4"	12"				15
	50	J - 4-1/2"	12.50"				15
	75	K - 4-5/8"	18"				15
	100	X - Special	19.50"				15
	125		19.75"				15
	150		20"				15
	200		29.50"				15
			30"				15
			36"				10
			39"				10
			40"				10
		50"	10				
		60"	10				
		70"	10				
		72"	10				

